

# TASK table

[xal.com/task](http://xal.com/task)



## Quickinfo

### GENERAL

table  
IP20

### LED

Mid-power LED  
up to 1030 lm  
3000 K, 4000 K  
CRI ≥ 80  
Binning initial ≤ 3 MacAdam

### ESTIMATED LED LIFETIME

L80/50 000 h

### OPTICAL

direct 100%

### ELECTRICAL

DIM via optical sensor (10-100%)  
movement sensor

### PHYSICAL


aluminium  
powder-coated  
head 360° rotatable, 15° tiltable

## Description


**DE** Schreibtischleuchte in puristischem Design und hoher Funktionalität; Leuchtenkopf 360° dreh- und 15° schwenkbar; Oberfläche weiß oder schwarz pulverbeschichtet; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; opale PMMA-Abdeckung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Binning initial ≤ 3 MacAdam; lieferbar in den Lichtfarben 3000 K und 4000 K; CRI ≥ 80; min. 80% des Lichtstromes nach 50 000 h Lebensdauer Schutzart IP20; SK II; stufenloses Dimmen via optischem Sensor (10-100% analog); integrierte USB-Ladebuchse zum Aufladen eines Smart Devices; Ausführung mit Präsenzmelder; Montage wahlweise auf Fußplatte, Tischklemmen oder Wand möglich

**EN** Desk lamp in puristic design with high functionality; lamp head 360° rotatable and 15° tiltable; surface powder coated in white or black; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 3000 K and 4000 K; CRI ≥ 80; min. 80% of the luminous flux after 50 000 hours; protection class IP20; PC II; continuously adjustable dimming via optical sensor (10-100% analog); integrated USB charging socket for charging of a smart device; version with presence detector optional; mounting possible on base plate, table clamps or wall

## Features



head 360° rotatable



head 15° tiltable



movement sensor



USB connector

### Standard configuration

COLOUR TEMPERATURE ⋮  
4000K  6

MATERIAL COLOUR ▣  
white  7



LIGHT OPTIC COVER  
opal

### Extended configuration

COLOUR TEMPERATURE ⋮  
3000K  5


MATERIAL COLOUR ▣  
black  8




+5% surcharges

### Options on request

COLOUR RENDERING INDEX  
CRI ≥ 90




### TASK table



#### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
12W	3000K	970lm	0 5 9 - 2 8 1 1 :: 7 <span style="color: blue;">▣</span> O
	4000K	1030lm	

#### LIGHT DISTRIBUTION



direct

### Accessories

#### BASE PLATE

TYPE	Ø-H (mm)	ORDER CODE
base plate	ø220 × 10	0 5 9 - 2 8 9 1 1 1 <span style="color: blue;">▣</span>

#### TABLE CLAMP FOR HOLE ø68mm


TYPE	Ø-H (mm)	ORDER CODE
table clamp	ø75 × 60	0 5 9 - 2 8 9 2 1 1 <span style="color: blue;">▣</span>

#### TABLE CLAMP

TYPE	L-W-H (mm)	ORDER CODE
table clamp	115 × 46 × 60	0 5 9 - 2 8 9 2 2 1 <span style="color: blue;">▣</span>

#### WALL FASTENING

TYPE	L-W-H (mm)	ORDER CODE
wall fastening	80 × 46 × 60	0 5 9 - 2 8 9 3 1 1 <span style="color: blue;">▣</span>



## Inspiration

XAL headquarters  
Graz, Austria

**PRODUCT**  
TASK table



