


D

Rundes Strahlerelement mit asymmetrisch strahlender Lichtkomponente
 Punktförmige Lichtquelle mit vorgesetzter Linseneinheit für präzise Ausblendung
 Lieferbar in Lichtfarbe 2700K
 Strahlerelement über Patentkugelschnapper drehbar am Montagering befestigt
 Asmo read: Taster am Leuchtgehäuse für Schaltung sowie Dimmung der Leuchte
 Lösung m. Rahmen auch als nicht drehbare Einheit ohne Patentkugelschnapper erhältl.
 Set für randlosen Einbau in Gipskartondecken 10-25mm oder
 Variante mit Rahmen für Einbau in Gipskartondecken 5-25mm in weiß erhältlich

E

Round spotlight with asymmetric radiant light component
 Punctual light source with lens unit in front of it for precise fade-out
 Available in 2700K
 Spotlight rotatable through patented ball catch system, attached to the mounting ring
 Asmo read: Pushbutton attached to mounting housing for circuit and dimming
 Solution also avail. with frame as non-rotatable unit without patented ball catch system
 Trimless mounting set for plasterboard ceilings 10-25mm or
 Optionally with frame for installing in plasterboard ceilings 5-25 mm, available in white

F

Projecteur rond avec lampe à faisceau assymétrique
 Source de lumière punctif. avec unité de lentille avancée pr fermeture en fondu précise
 Disponible dans la température de couleur 2700K
 Projecteur sur clip à bille patenté, pivotable, accroché à L'anneau de montage
 Asmo read: interrupteur sur l'encastré pour allumage on/off ou graduation
 Solution aussi disp. a. cadre comme unité non pivotable sans système de clip à bille
 Kit pour encastrement sans rebord dans les plafonds en plaque de plâtre
 Var. a. cadre p. encastrem. dans plafonds en plaques de plâtre 5-25 mm disp. en blanc

TYPE			
	 100 ø 110	cob LED TYPE 7W LED 480 lm* non DIM 220-240V	ASMO FIX with trim TYPE 7W LED 480 lm* non DIM CODE 048-0821417
	 110 360° 106 144 ø 100 ø 98	cob LED TYPE 7W LED 480 lm* non DIM 220-240V	ASMO TURN trimless TYPE 7W LED 480 lm* non DIM CODE 048-0831417
	 108 ø 112 ø 96	cob LED TYPE 7W LED 480 lm* non DIM 220-240V	ASMO TURN with trim TYPE 7W LED 480 lm* non DIM CODE 048-0841417
	 110 360° 106 144 ø 100 ø 98	e ² LED TYPE 5W LED 220 lm* integrated push-button 220-240V	ASMO READ TURN trimless TYPE 5W LED 220 lm* integrated push-button CODE 048-0931457
	 108 360° ø 112 ø 98	e ² LED TYPE 5W LED 220 lm* integrated push-button 220-240V	ASMO READ TURN with trim TYPE 5W LED 220 lm* integrated push-button CODE 048-0941457

*System power | Luminous flux 3000K

PHOTOMETRIC DATA


See page 659 for photometric data

ADDITIONAL INFORMATION


See page 040 for recessed luminaire

▶ PRIVATE RESIDENCE, GRAZ
Architect: INNOCAD, Graz

