

PH 4/3 Table

Weblink: 1588

Design: Poul Henningsen

Light Concept: The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of metal and painted white to ensure diffuse, comfortable light distribution.

Finish: White or white, wet painted. High lustre chrome plated.

Material: Shades: Spun aluminium. Base: High lustre chrome plated, spun brass. Stem: High lustre chrome plated, steel. Triangular piece: Black sandblasted, injection moulded bakelite.

Mounting: Cable type: Plastic cord with plug. Cable length: 2.9m. Light control: Switch in lamp stand.

Weight: Max. 2kg.

Class: Ingress protection IP20. Electric shock protection II w/o ground.



Product code	Light source	Finish
PH43-T	1x100W E27	WHT

Specification notes:
The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispuolsen.com we update a list of recommendable light sources.



PH 80

Weblink: 1590

Design: Poul Henningsen

Lighting Concept: The fixture emits diffuse and symmetrical light. The majority of the light is directed downwards, and the opal acrylic shades provide comfortable room lighting. The red hue of the top reflector helps giving the light a warmer glow.

Finish: White opal acrylic. High lustre chrome plated.

Material: Shades: High pressure moulded white opal acrylic. Top shade: Black, high pressure moulded polycarbonate. Base: Black, high pressure moulded ABS. Stem: High lustre chrome plated, steel.

Mounting: Cable type: Plastic cord with plug. Cable length: 2.6m. Light control: On/off switch on cord.

Weight: Max. 7.5kg.

Class: Ingress protection IP20. Electric shock protection II w/o ground.



Product code	Light source	Finish
PH80-F	1x100W E27	WHT OPAL ACRYL

Specification notes:
The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispuolsen.com we update a list of recommendable light sources.

