

POPCORN 3S



POPCORN 3S

LUMINAIRE

SMALL AND COMPACT
 SUPER INTENSE 8W SINGLE LED LIGHT SOURCE
 ANTI-GLARE OPTIONS FOR VISUAL COMFORT
 VERSATILE MOUNTING SYSTEM
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS
 CONTROLLABLE USING 1-10V, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE
 HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES


- CLASSIC
- 01 DOUBLE-ANODISED ALUMINIUM
 - 02 BLACK ALUMINIUM
 - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
 - 04 POLISHED COPPER

SPECIAL BY REQUEST

PHOTOMETRY

LUX @ / BEAM	16°	21°	26°	45°
1M	5258	2259	1990	903
2M	1314	565	497	226
3M	584	251	221	100
4M	329	141	124	56
5M	210	90	80	36
DELIVERED LUMENS	562LM	526LM	526LM	483LM

TEST CONDITION: 2700K, 700MA, 8W, CLEAR GLASS, w/o VISUAL COMFORT



LIGHT CONFIGURATOR ENGINE: PC3SS

POWER 4W 8W

BEAM 16°* 21° 26° 45° 28°x49° *10MM TALLER

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR FR FROSTED HF HALF FROSTED HB HALF BLACK

IP IP20 IP67 IP68 (316L ONLY)

FINISHES 01 AL 0.6KG 02 AL 0.6KG 03 316L SS 1.2KG 04 CU 1.2KG

INCLUDED • U-BRACKET, 3000MM CABLE LENGTH

- OPTIONS
- | | | |
|--|--|--|
| / VISUAL COMFORT | / VERSATILE MOUNTING | / REMOTE DRIVER |
| <input type="checkbox"/> HOOD (PG 132) | <input type="checkbox"/> SPIKE (PG 140) | <input type="checkbox"/> VERSA (PG 147) |
| <input type="checkbox"/> SNOOT (PG 133) | <input type="checkbox"/> PLATE (PG 141) | <input type="checkbox"/> DRIVE (PG 148) |
| <input type="checkbox"/> SNOOT w/o HOLES (PG 133) | <input type="checkbox"/> BASE (PG 141) | <input type="checkbox"/> CV CONVERTER (PG 151) |
| <input type="checkbox"/> DARK (PG 134) | <input type="checkbox"/> WONDER BAR 600MM (PG 142) | |
| <input type="checkbox"/> DARK w BLACKOUT RING (PG 134) | <input type="checkbox"/> WONDER BAR 1200MM (PG 142) | / IP68 CONNECTOR |
| <input type="checkbox"/> HONEYCOMB (PG 137) | <input type="checkbox"/> STRAP ON w 1 ADAPTOR (PG 143) | <input type="checkbox"/> 2 POLE |
| | ADDITIONAL ADAPTOR QTY _____ | <input type="checkbox"/> 4 POLE |

