

POPSTER 2 TURBO



POPSTER 2 TURBO

LUMINAIRE

HYBRID CONSTRUCTION
 SUPER SMALL AND COMPACT
 SUPER INTENSE 2W SINGLE LED LIGHT SOURCE
 HIGH POWER-TO-SIZE RATIO
 BUILT IN VISUAL COMFORT
 VERSATILE MOUNTING SYSTEM
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 POLYCARBONATE COVER
 CONTROLLABLE USING 1-10V, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE
 HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST


FINISHES

- NEW
- 01 DOUBLE-ANODISED ALUMINIUM
w/ SILVER POLYCARBONATE
 - 02 BLACK ALUMINIUM
w/ BLACK POLYCARBONATE
 - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
w/ SILVER POLYCARBONATE

PHOTOMETRY

LUX @ / BEAM	10°	16°	29°	44°
1M	2674	1557	566	235
2M	661	390	142	59
3M	295	173	63	26
4M	165	97	35	14
5M	105	63	23	10
DELIVERED LUMENS	192LM	181LM	150LM	127LM

TEST CONDITION: 2700K, 700MA, 2W, CLEAR GLASS, w/o VISUAL COMFORT



LIGHT CONFIGURATOR ENGINE: PS2TS

POWER 2W

BEAM 10° 16° 29° 44°

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

COVER CLEAR POLYCARBONATE

IP IP20 IP67 IP68 (316L ONLY)

FINISHES 01 AL 0.1KG 02 AL 0.1KG 03 316L 0.2KG

INCLUDED U-BRACKET, 3000MM CABLE LENGTH

- OPTIONS
- / VISUAL COMFORT
 - HONEYCOMB (PG 137)
 - / VERSATILE MOUNTING
 - DUO (PG 140)
 - SPIKE (PG 140)
 - PLATE (PG 141)
 - BASE (PG 141)
 - ULTRA BASE (PG 142)
 - WONDER BAR 600MM (PG 142)
 - WONDER BAR 1200MM (PG 142)
 - STRAP ON w/ 1 ADAPTOR (PG 143)
 - / REMOTE DRIVER
 - VERSA (PG 147)
 - DRIVE (PG 148)
 - CV CONVERTER (PG 151)
 - / IP68 CONNECTOR
 - 2 POLE
 - 4 POLE
- ADDITIONAL ADAPTOR QTY _____

