

**SUPERDARK 2 TURBO**



**SUPERDARK 2 TURBO**

**LUMINAIRE**

- DARK LIGHTER
- SUPER SMALL & COMPACT
- SUPER INTENSE 2W SINGLE LED LIGHT SOURCE
- HIGH POWER-TO-SIZE RATIO
- VERSATILE MOUNTING SYSTEM
- SURFACE TREATED FOR EXTREME CONDITIONS
- HIGH CORROSION RESISTANT
- TOUGHENED SAFETY GLASS
- CONTROLLABLE USING 1-10V, DALI OR DMX DRIVERS

**PERFORMANCE**

- INTELLIMODE OPTION
- HOT TESTED & COLOUR BINNED AT Tj 85°C
- EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
- HIGH POWER LM80 COMPLIANT LED
- CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

**FINISHES**

- CLASSIC
- 01 DOUBLE-ANODISED ALUMINIUM
  - 02 BLACK ALUMINIUM
  - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
  - 04 POLISHED COPPER

SPECIAL BY REQUEST

**PHOTOMETRY**

LUX @ / BEAM	10°	16°	29°
1M	1850	1288	876
2M	463	322	219
3M	206	143	97
4M	116	80	54
5M	74	52	35

DELIVERED LUMENS 126LM 135LM 149LM

TEST CONDITION: 2700K, 700MA, 2W, CLEAR GLASS



**LIGHT CONFIGURATOR** ENGINE: SD2TS

POWER  2W  INTELLIMODE (12MM TALLER)

BEAM  10°  16°  29°

CCT  2700K  3000K  4000K  5000K  BLUE  OTHERS

GLASS  CL CLEAR  CLD CLEAR + SOFT EDGE DEVICE

IP  IP20  IP67  IP68 (316L ONLY)

FINISHES  01 AL 0.3KG  02 AL 0.3KG  03 316L SS 0.6KG  04 CU 0.6KG

INCLUDED  U-BRACKET, 3000MM CABLE LENGTH

- OPTIONS
- / VERSATILE MOUNTING
    - DUO (PG 140)
    - SPIKE (PG 140)
    - PLATE (PG 141)
    - BASE (PG 141)
    - ULTRA BASE (PG 142)
    - WONDER BAR 600MM (PG 142)
    - WONDER BAR 1200MM (PG 142)
    - STRAP ON w 1 ADAPTOR (PG 143)
    - ADDITIONAL ADAPTOR QTY \_\_\_\_\_
  - / REMOTE DRIVER
    - VERSA (PG 147)
    - DRIVE (PG 148)
    - CV CONVERTER (PG 151)
  - / IP68 CONNECTOR
    - 2 POLE
    - 4 POLE

