

SUPERDARK 3S



SUPERDARK 3S

LUMINAIRE

DARK LIGHTER
 SMALL AND COMPACT
 SUPER INTENSE 8W SINGLE LED LIGHT SOURCE
 VERSATILE MOUNTING SYSTEM
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS
 CONTROLLABLE USING 1-10V, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE
 HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES

- CLASSIC
- 01 DOUBLE-ANODISED ALUMINIUM
 - 02 BLACK ALUMINIUM
 - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
 - 04 POLISHED COPPER


SPECIAL BY REQUEST

PHOTOMETRY

LUX @ / BEAM	16°	21°	26°
1M	2614	2011	1952
2M	654	503	488
3M	291	224	217
4M	164	126	122
5M	104	80	78

DELIVERED LUMENS 402LM 335LM 315LM

TEST CONDITION: 2700K, 700MA, 8W, CLEAR GLASS



LIGHT CONFIGURATOR ENGINE: SD3SS

POWER 4W 8W

BEAM 16°* 21° 26° *10MM TALLER

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR CLD CLEAR + SOFT EDGE DEVICE

IP IP20 IP67 IP68 (316L ONLY)

FINISHES 01 AL 0.6KG 02 AL 0.6KG 03 316L SS 1.2KG 04 CU 1.2KG

INCLUDED • U-BRACKET, 3000MM CABLE LENGTH

- OPTIONS
- / VERSATILE MOUNTING
 - SPIKE (PG 140)
 - PLATE (PG 141)
 - BASE (PG 141)
 - ULTRA BASE (PG 142)
 - WONDER BAR 600MM (PG 142)
 - WONDER BAR 1200MM (PG 142)
 - STRAP ON w 1 ADAPTOR (PG 143)
 - / REMOTE DRIVER
 - VERSA (PG 147)
 - DRIVE (PG 148)
 - CV CONVERTER (PG 151)
 - / IP68 CONNECTOR
 - 2 POLE
 - 4 POLE
- ADDITIONAL ADAPTOR QTY _____

