

POPCAN 2 TURBO



POPCAN 2 TURBO

LUMINAIRE

SETBACK LIGHT SOURCE FOR VISUAL COMFORT
 INTEGRATED NON-DIMMABLE DRIVER
 SUPER INTENSE 2W SINGLE LED LIGHT SOURCE
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS

PERFORMANCE

HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST


FINISHES

CLASSIC 01 DOUBLE-ANODISED ALUMINIUM
 02 BLACK ALUMINIUM
 SPECIAL BY REQUEST

PHOTOMETRY

LUX @ BEAM	10°	16°	29°	44°
1M	2786	1639	596	247
2M	696	410	149	62
3M	310	182	66	27
4M	174	102	37	15
5M	111	66	24	10
DELIVERED LUMENS	202LM	190LM	158LM	134LM

TEST CONDITION: 2700K, 700MA, 2W, CLEAR GLASS



LIGHT CONFIGURATOR ENGINE: PN2TI

POWER 2W

BEAM 10° 16° 29° 44°


CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR

IP IP20 IP67

FINISHES 01 AL 0.6KG 02 AL 0.6KG

INCLUDED INTEGRATED NON-DIMMABLE DRIVER SURFACE MOUNTING KIT



POPCAN 2 TURBO



maerich.com | 49

POPCAN 3 TURBO



POPCAN 3 TURBO

LUMINAIRE

SETBACK LIGHT SOURCE FOR VISUAL COMFORT
 INTEGRATED NON-DIMMABLE DRIVER
 SUPER INTENSE 6W OR 8W LED LIGHT SOURCE
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS

PERFORMANCE

HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI >80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES


CLASSIC 01 DOUBLE-ANODISED ALUMINIUM
 02 BLACK ALUMINIUM

 SPECIAL BY REQUEST

PHOTOMETRY

LUX @ BEAM	10°	16°	29°	44°
1M	7652	4547	1965	714
2M	1913	1137	491	178
3M	850	505	218	79
4M	478	284	123	45
5M	306	182	79	29
DELIVERED LUMENS	549LM	545LM	525LM	430LM

TEST CONDITION: 2700K, 700MA, 6W, CLEAR GLASS



LIGHT CONFIGURATOR ENGINE: PN3TI

POWER 6W (3 X 2W) 8W (4 X 2W)

BEAM 10° 16° 29° 44°


CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR

IP IP20 IP67

FINISHES 01 AL 1.3KG 02 AL 1.3KG

INCLUDED INTEGRATED NON-DIMMABLE DRIVER SURFACE MOUNTING KIT



POPCAN 3 TURBO



POPCAN 3S



POPCAN 3S

LUMINAIRE

SETBACK LIGHT SOURCE FOR VISUAL COMFORT
 INTEGRATED NON-DIMMABLE DRIVER
 SUPER INTENSE 8W SINGLE LED LIGHT SOURCE
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS

PERFORMANCE

HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI >80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES


CLASSIC 01 DOUBLE-ANODISED ALUMINIUM
 02 BLACK ALUMINIUM

 SPECIAL BY REQUEST

PHOTOMETRY

LUX @ / BEAM	16°	21°	26°	45°
1M	5258	2259	1990	903
2M	1314	565	497	226
3M	584	251	221	100
4M	329	141	124	56
5M	210	90	80	36
DELIVERED LUMENS	562LM	526LM	526LM	483LM

TEST CONDITION: 2700K, 700MA, 8W, CLEAR GLASS



LIGHT CONFIGURATOR ENGINE: PN3SI

POWER 4W 8W

BEAM 16° 21° 26° 45°

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR

IP IP20 IP67

FINISHES 01 AL 1.3KG 02 AL 1.3KG

INCLUDED INTEGRATED NON-DIMMABLE DRIVER SURFACE MOUNTING KIT

