

POPCORN SUPERSPOT



POPCORN SUPERSPOT

LUMINAIRE

NARROW 8° BEAM
 SMALL AND COMPACT
 SUPER INTENSE 2W SINGLE LED LIGHT SOURCE
 ANTI-GLARE OPTIONS FOR VISUAL COMFORT
 VERSATILE MOUNTING SYSTEM
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS
 CONTROLLABLE USING 1-10V, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE
 HOT TESTED & COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES

CLASSIC 01 DOUBLE-ANODISED ALUMINIUM
 02 BLACK ALUMINIUM
 03 ELECTRO-POLISHED 316L STAINLESS STEEL
 04 POLISHED COPPER
 SPECIAL BY REQUEST

PHOTOMETRY

LUX @ / BEAM	8°
1 M	7553
2M	1888
3M	839
4M	472
5M	302
DELIVERED LUMENS	222LM

TEST CONDITION: 2700K, 700MA, 2W, CLEAR GLASS, w/o VISUAL COMFORT



LIGHT CONFIGURATOR ENGINE: SS2TS

POWER 2W

BEAM 8°

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CL CLEAR

IP IP20 IP67 IP68 (316L ONLY)

FINISHES 01 AL 0.3KG 02 AL 0.3KG 03 316L SS 0.6KG 04 CU 0.6KG

INCLUDED U-BRACKET, 3000MM CABLE LENGTH

OPTIONS	/ VISUAL COMFORT	/ VERSATILE MOUNTING	/ REMOTE DRIVER
<input type="checkbox"/> HOOD	(PG 132)	<input type="checkbox"/> SPIKE	(PG 140)
<input type="checkbox"/> SNOOT	(PG 133)	<input type="checkbox"/> PLATE	(PG 141)
<input type="checkbox"/> SNOOT w/o HOLES	(PG 133)	<input type="checkbox"/> BASE	(PG 141)
<input type="checkbox"/> DARK	(PG 134)	<input type="checkbox"/> ULTRA BASE	(PG 142)
<input type="checkbox"/> DARK w BLACKOUT RING	(PG 134)	<input type="checkbox"/> WONDER BAR 600MM	(PG 142)
<input type="checkbox"/> HONEYCOMB	(PG 137)	<input type="checkbox"/> WONDER BAR 1200MM	(PG 142)
		<input type="checkbox"/> STRAP ON w 1 ADAPTOR	(PG 143)
		ADDITIONAL ADAPTOR QTY	_____
			/ IP68 CONNECTOR
			<input type="checkbox"/> 2 POLE
			<input type="checkbox"/> 4 POLE

