


POPEYE 1/2 TURBO / POPEYE 2/3 TURBO



POPEYE 1/2 TURBO
POPEYE 2/3 TURBO

LUMINAIRE

HIGH VISUAL COMFORT WITH MINIMAL LIGHT LOSS
MINIMAL SET OUT FROM INTENDED LIGHT UP SURFACE
SURFACE GRAZER
SUPER INTENSE FORWARD LIGHT THROW
SUPER SMALL AND COMPACT
SCREWLESS FACEPLATE
SURFACE TREATED FOR EXTREME CONDITIONS
HIGH CORROSION RESISTANT
TOUGHENED SAFETY GLASS
CONTROLLABLE USING 1-10, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE OPTION
HOT TESTED AND COLOUR BINNED AT Tj 85°C
EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
HIGH POWER LM80 COMPLIANT LED
CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST


FINISHES

- BODY** 02 BLACK ALUMINIUM
03 ELECTRO-POLISHED 316L STAINLESS STEEL
- CLASSIC** 01 DOUBLE-ANODISED ALUMINIUM
- TRIM** 02 BLACK ALUMINIUM
03 ELECTRO-POLISHED 316L STAINLESS STEEL
04 POLISHED COPPER
- 06 'TITANIUM GREY' ALUMINIUM
07 'GRAPHITE BLACK' ALUMINIUM
08 BLACK 316L STAINLESS STEEL

PHOTOMETRY

LUX @ / BEAM	1/2 EYE
1M	210
2M	53
3M	23
4M	13
5M	8
DELIVERED LUMENS	78LM

TEST CONDITION: 2700K, 700MA, 2W, DOUBLE FROSTED GLASS



LIGHT CONFIGURATOR ENGINE: PE2TR

POWER 2W INTELLIMODE (12MM DEEPER)

BEAM ASYMMETRIC

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS DF DOUBLE FROSTED

IP IP20 IP67 IP68 (316L ONLY)

BODY 02 AL 0.2KG 03 316L SS 0.4KG

TRIM 01 AL 02 AL 03 316L SS 04 CU 06 AL 07 AL 08 316L SS

FACEPLATE / POPEYE 1/2 / POPEYE 2/3
1/2 2/3

INCLUDED / CEILING RECESSED / RECESSED
WINGS, 300MM CABLE LENGTH (AL ONLY) FOR IP67, NICHE S1 600MM CABLE LENGTH
= 44MM FOR IP68, NICHE F1 w/ ENDCAP 3000MM CABLE LENGTH

OPTIONS / REMOTE DRIVER / IP68 CONNECTOR
VERS (PG 147) 2 POLE
DRIVE (PG 148) 4 POLE
CV CONVERTER (PG 151)

