


POPPY 'C' 3S / POPPY 'O' 3S



POPPY 'C' 3S / POPPY 'O' 3S

LUMINAIRE

DEEP SET LIGHT SOURCE FOR EXTREME VISUAL COMFORT  
 'C' FOR CIRCULAR 12° PINHOLE  
 'O' FOR OVAL 12°X16° PINHOLE  
 SUPER INTENSE 8W SINGLE LED LIGHT SOURCE  
 HIGH POWER-TO-SIZE RATIO  
 UPLIGHTER AND DOWNLIGHTER  
 SURFACE TREATED FOR EXTREME CONDITIONS  
 HIGH CORROSION RESISTANT  
 TOUGHENED SAFETY GLASS  
 CONTROLLABLE USING 1-10, DALI OR DMX DRIVERS

PERFORMANCE


INTELLIMODE  
 HOT TESTED AND COLOUR BINNED AT Tj 85°C  
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN  
 HIGH POWER LM80 COMPLIANT LED  
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES

- BODY**
- 02 BLACK ALUMINIUM
  - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
- CLASSIC**
- 01 DOUBLE-ANODISED ALUMINIUM
- TRIM**
- 02 BLACK ALUMINIUM
  - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
  - 04 POLISHED COPPER
- SPECIAL**
- 05 WHITE POWDER COATED ALUMINIUM
- TRIM**
- 06 'TITANIUM GREY' ALUMINIUM
  - 07 'GRAPHITE BLACK' ALUMINIUM
  - 08 BLACK 316L STAINLESS STEEL

PHOTOMETRY

LUX @ / BEAM	C
1M	2437
2M	609
3M	271
4M	152
5M	98
DELIVERED LUMENS	251LM
TEST CONDITION: 2700K, 700MA, 8W, CLEAR GLASS	



LIGHT CONFIGURATOR ENGINE: PP3SR

POWER  4W  8W

BEAM / POPPY 'C' 3S / POPPY 'O' 3S  
 12°  12°X16°

CCT  2700K  3000K  4000K  5000K  BLUE  OTHERS

GLASS  CL CLEAR

IP  IP20  IP67  IP68 (316L ONLY)

BODY  02 AL 0.4KG  03 316L SS 0.8KG

TRIM  01 AL  02 AL  03 316L SS  04 CU  05 AL  06 AL  07 AL  08 316L SS

FACEPLATE / POPPY 'C' 3S / POPPY 'O' 3S  
 RT ROUND  ST SQUARE PG145  3T SIXSOME 250MM PG144  6T SIXSOME 500MM PG144  RT ROUND

INCLUDED / CEILING RECESSED / RECESSED  
 WINGS, 300MM CABLE LENGTH (AL ONLY)  FOR IP67, NICHE S3 600MM CABLE LENGTH  
  $\frac{1}{2}$  = 69MM  FOR IP68, NICHE S3 w/ ENDCAP 3000MM CABLE LENGTH

OPTIONS / REMOTE DRIVER / IP68 CONNECTOR  
 VERSA (PG 147)  CV CONVERTER (PG 151)  2 POLE  
 DRIVE (PG 148)  4 POLE

