

POPPY 'C' TURBO / POPPY 'O' TURBO



POPPY 'C' TURBO / POPPY 'O' TURBO

LUMINAIRE

DEEP SET LIGHT SOURCE FOR EXTREME VISUAL COMFORT
 'C' FOR CIRCULAR 8° PINHOLE
 'O' FOR OVAL 8°X10° PINHOLE
 UPLIGHTER AND DOWNLIGHTER
 SUPER SMALL & COMPACT
 SCREWLESS FACE PLATE
 SURFACE TREATED FOR EXTREME CONDITIONS
 HIGH CORROSION RESISTANT
 TOUGHENED SAFETY GLASS
 CONTROLLABLE USING 1-10, DALI OR DMX DRIVERS

PERFORMANCE

INTELLIMODE OPTION
 HOT TESTED AND COLOUR BINNED AT Tj 85°C
 EXCELLENT COLOUR CONSISTENCY USING SINGLE BIN
 HIGH POWER LM80 COMPLIANT LED
 CRI > 80, HIGHER CRI AVAILABLE UPON REQUEST

FINISHES

- BODY**
- 02 BLACK ALUMINIUM
 - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
- CLASSIC TRIM**
- 01 DOUBLE-ANODISED ALUMINIUM
 - 02 BLACK ALUMINIUM
 - 03 ELECTRO-POLISHED 316L STAINLESS STEEL
 - 04 POLISHED COPPER
- SPECIAL TRIM**
- 05 WHITE POWDER COATED ALUMINIUM
 - 06 'TITANIUM GREY' ALUMINIUM
 - 07 'GRAPHITE BLACK' ALUMINIUM
 - 08 BLACK 316L STAINLESS STEEL

PHOTOMETRY

LUX @ / BEAM	C
1M	649
2M	162
3M	72
4M	41
5M	26
DELIVERED LUMENS	48LM

TEST CONDITION: 2700K, 700MA, 2W, CLEAR GLASS



LIGHT CONFIGURATOR ENGINE: PP2TR

POWER 2W INTELLIMODE (12MM DEEPER)

BEAM / POPPY 'C' / POPPY 'O'

8° / 8°X10°

CCT 2700K 3000K 4000K 5000K BLUE OTHERS

GLASS CLEAR

IP IP20 IP67 IP68 (316L ONLY)

BODY 02 AL 0.3KG 03 316L SS 0.6KG

TRIM 01 AL 02 AL 03 316L SS 04 CU 05 AL 06 AL 07 AL 08 316L SS

FACEPLATE / POPPY 'C' / POPPY 'O'

RT ROUND ST SQUARE PG145 3T SIXSOME 250MM PG144 6T SIXSOME 500MM PG144 RT ROUND

INCLUDED / CEILING RECESSED / RECESSED

WINGS, 300MM CABLE LENGTH (AL ONLY) FOR IP67, NICHE S1 600MM CABLE LENGTH
 = 44MM FOR IP68, NICHE F1 w ENDCAP 3000MM CABLE LENGTH

OPTIONS / REMOTE DRIVER / IP68 CONNECTOR

VERSA (PG 147) CV CONVERTER (PG 151) 2 POLE
 DRIVE (PG 148) 4 POLE

